



Reliability



Flexibility



Easy to use



- Metal body, beautiful and long durable
- Plug and play 1s installation, no need to set
- Support local and remote monitoring
- IP65, for both indoor and outdoor installation

- External SIM card slot, easier for SIM card replacement
- External antenna, stronger signal and reliable communication
- Enable mobile monitoring at anytime anywhere

Technical Parameters

General Data	
Max. No. of Inverters	1
Inverter Communication	USB3.0
External Antenna	SMA water-proof glue stick antenna
Data Intervals	Remote configuration available
Preference Setting	Remote Web、APP
Data Access	Remote server
Working Voltage (V)	DC 5
Working Current (mA)	130 (600 Peak)
Wireless Data	
Wireless Transmitting Power (dbm)	GSM850/EGSM900: 5 ~ 32.5、DCS1800/PCS1900: 0 ~ 29.5
Wireless Receiving Sensitivity (dBm)	< -108.5
Wireless Operating Frequency	GSM850, EGSM900, DCS1800, PCS1900
GPRS Connection Features	GPRS multi-slot class is 10 (default), GPRS mobile station class B
Environmental Data	
Operating Temperature (°C)	-10~+60
Operating Humidity (%)	0-90 relative humidity, no condensation
Storage Temperature (°C)	-40~+85
Storage Humidity (%)	< 40
Protection Degree	IP65
Other Data	
Dimensions (mm)	156L*52W*30H
Weight (g)	140
Certificates	SRRC
Warranty	2 years